

Technical Data Sheet

W610 – High Stability Gloss Duct Emulsion

- A premium high gloss emulsion suitable for application via the spare ink duct inline over conventional inks
- Exhibiting excellent rub resistance
- Specially formulated for stability through the ink duct.
- Suitable for subsequent after processing

Applications

W610 has been designed for use on commercial print and packaging work, in-line over conventional ink.

Single / Double Sided	Single
Heat Resistance	<=110°C
Foil Blockable/Glueable	Yes – test first

Properties

Viscosity (Din6 @ 25°C)	70-85 seconds
Gloss	Very High
pH	7.5 – 8.5
Resolubility	High
Scuff/Rub	High
Slip	ST 0.40 – 0.45
Solids	50% +/-2

Substrate

W610 has been designed for use on most paper and board substrates.

We recommend to trial test the use of this product on low grammage stocks (<115GSM).

Machine / Printing

W610 is suitable for application via the majority of conventional machines, including Heidelberg, Komori, KBA, manroland, Mitsubishi and Ryobi.

It is recommended that the press is equipped with some form of accelerated drier such as hot air knives.

Storage and Shelf Life

- Store in temperatures not exceeding 30°C and not falling below 5°C!
- Store on either pallets or racking in order to protect from cold floors.
- Protect from frost
- If left unopened and kept in the correct conditions Waterbased products have a shelf life of 12 months.

Note

The information contained in this data sheet corresponds with our current knowledge and experience. The liability for the application and processing of our products lies with the buyer, who is also responsible for observing the third party rights.

We reserve the right to alter any of these details as a result of technical or manufacturing developments.

For any further information please contact the technical department at ECS (Nottingham) LTD

Issued: 29.06.10